



PRODUCT CATALOGUE

AUSTRALIAN MADE FOR AN AUSTRALIAN LIFESTYLE

PRODUCT DETAILS

DeltaBeam™ - Steel Beams

- Manufactured from strong high tensile steel for long unsupported spans
- DeltaXtremeBeam™ is available in 250mm & 300mm for extra long unsupported spans
- Beams are cut to length
- Forms part of a full patio suite along with post kits and extender brackets
- End caps folded to suit each beam size

DeltaBeam™ - Aluminium Beams

- Manufactured in 6063-T5 grade aluminium and powder coated to suit a full range of contemporary colours
- Available in both 150mm and 200mm
- Forms part of the Coastal Range of aluminium products that are designed for Marine and other highly corrosive environments.
- Available in set lengths
- Die-cast aluminium end-caps to provide a clean tidy finish

WARRANTY

- All DeltaBeams™ are covered by our standard 20 year warranty with site specific warranties available on request. Please refer to the warranty conditions as outlined on our web page.





DELTABEAM™ SPECIFICATIONS / STEEL BEAM RANGE

Manufactured from high tensile steel, DeltaBeam™ is engineered and tested to comply with Australian Standard 1397/G550. Major components are made from strong high tensile steel, while the fixings and brackets are galvanised for a long, useable life.

DELTABEAM™ SPECIFICATIONS

	100	150	200	250	300
Base Metal Thickness	1.0mm	1.2mm	1.2mm	1.6mm	1.6mm
Yield Strength	550MPa	550MPa	550MPa	550MPa	550MPa
Mass	4.1kg/m	5.7kg/m	7.8kg/m	10.4kg/m	11.7kg/m


* Refer to Delta Span Tables for design and spanning details.

COLOUR AVAILABILITY

	100	150	200	250	300
Off White/Surfmist®	•	•	•	•	•
Night Sky/Ebony™	•	•	•	•	•

DeltaBeam™ is manufactured in 80% gloss colours
 ® Colour names are registered trademarks of Bluescope Steel Limited
 ™ Colour names are registered trademarks of Bluescope Steel Limited

DELTABEAM™ DIMENSIONS / STEEL BEAM RANGE





DELTABEAM™ SPECIFICATIONS / ALUMINIUM BEAM RANGE

Manufactured from Aluminium Alloy 6063-T5 and designed with a 5mm Base and Top with a fluted Side Wall of 3mm to provide for maximum spanning capacity. They are extruded to give a precise finished profile and are specifically designed to be used in Coastal & Marine Environments to combat the corrosive nature of exposure to saltwater.


DELTABEAM™ SPECIFICATIONS		
	150	200
Base Metal Thickness Side Walls	3mm	3mm
Base Metal Thickness Base & Top	5mm	5mm
Mass	4.2kg/lm	5.0kg/lm

** Refer to Delta Span Tables for design and spanning details.*

COLOUR AVAILABILITY		
	150	200
Off White/Surfmist®	•	•
Night Sky/Ebony™	•	•

DeltaBeam™ is manufactured in 80% gloss colours
 ® Colour names are registered trademarks of Bluescope Steel Limited
 ™ Colour names are registered trademarks of Bluescope Steel Limited

DELTABEAM™ DIMENSIONS / ALUMINIUM BEAM RANGE






DELTA

EXTENDER ROOF POST KIT

AVAILABLE IN BOTH STEEL & ALUMINIUM




Extender Post

Delta - Extender Post Kit

Available in 600mm & 800mm

Consisting of: -

- 1 x 75mm x 75mm x 4mm SHS Galvanised Post
- 1 x Extender Foot Bracket
- 1 x Decktite Rubber Seal



Extender Foot Bracket

1 x G300 4mm thick
65mm x 65mm x 170mm
welded receiver upright

1 x G300 Fixing Plate
4mm thick x 145mm x 75mm
welded to the receiver upright



Decktite

ROOF EXTENDA BRACKET

ALUMINIUM BEAM - END CAPS



MKII Roof Extenda Bracket

Available in S300, S400 & S500 sizes

Consisting of:-

- Top Bracket
- Bottom Bracket
- Locking Hex Nut
- FlashRite Weather Seal

