

Delta Cool TPC Panel Serviceability (L/150) Load Tables (kPa)					
Span	Thickness (mm)				
	50	75	100	150	200
1800	1.197	1.270	1.342		
2100	1.094	1.185	1.275		
2400	0.997	1.103	1.210	1.253	
2700	0.906	1.026	1.146	1.221	
3000	0.821	0.952	1.083	1.190	
3300	0.742	0.882	1.022	1.159	
3600	0.669	0.816	0.963	1.127	
3900	0.603	0.754	0.905	1.096	1.271
4200	0.542	0.695	0.848	1.064	1.247
4500	0.487	0.640	0.793	1.033	1.219
4800	0.438	0.589	0.739	1.002	1.187
5100	0.395	0.541	0.687	0.970	1.171
5400	0.358	0.497	0.637	0.939	1.127
5700	0.327	0.458	0.588	0.907	1.087
6000	0.302	0.421	0.540	0.876	1.067
6300	0.283	0.389	0.494	0.844	1.037
6600	0.270	0.360	0.450	0.813	1.007
6900	0.264	0.335	0.407	0.781	0.977
7200		0.183	0.365	0.750	0.947
7500		0.163	0.325	0.718	0.917
7800		0.143	0.287	0.687	0.887
8100		0.125	0.250	0.655	0.857
8400		0.107	0.214	0.624	0.827
8700		0.090	0.180	0.592	0.797
9000		0.074	0.148	0.561	0.767
9300			0.117	0.529	0.737
9600			0.087	0.498	0.707
9900			0.059	0.466	0.677
10200				0.435	0.647
10500				0.403	0.617