

# Bushfire test on an external wall system

## Test Report

**Author:** Chris Wojcik  
**Report number:** FSZ 2373  
**Date:** 9 June 2023

**Clients:** Delta Panels Pty Ltd

Commercial-in-confidence

### Fire Testing and Assessments

Infrastructure Technologies  
14 Julius Avenue  
North Ryde, NSW 2113  
Telephone +61 2 9490 5444

### Author

Infrastructure Technologies  
14 Julius Avenue  
North Ryde, NSW 2113  
Telephone +61 2 9490 5500




### The Client

Delta Panels Pty Ltd  
731 Boundary Road  
Richlands, QLD 4077  
Telephone +61 7 3271 2170

### Report Status and Revision History:

VERSION	STATUS	DATE	DISTRIBUTION	ISSUE NUMBER
Draft	Draft	05/06/2023	CSIRO/Client	FSZ 2373
	Final for issue	09/06/2023	CSIRO/Client	FSZ 2373

### Report Authorization:

AUTHOR	REVIEWED BY	AUTHORISED BY
Chris Wojcik	Keith Nicholls	Brett Roddy
		
9 June 2023	9 June 2023	9 June 2023

## Use of this Report

### **Use of Reports – Testing**

*This report is subject to binding obligations under which it was prepared. In particular, the Report must not be used:*

- *as a means of endorsement; or*
- *in a company prospectus or notification to a Stock Exchange document for capital raising, without the prior written consent of CSIRO.*

*The Report may be published verbatim and in full, provided that a statement is included on the publication that it is a copy of the Report issued by CSIRO.*

*Excerpts of the Report may not be published.*

### **Use of Reports – Consultancy**

*This report is subject to binding obligations under which it was prepared. In particular, the Report may only be used for the following purposes:*

- *the information in the Report may be used by the party that commissioned the Report for its internal business operations (but not licensing to third parties);*
- *the report may be copied for distribution within the organisation that commissioned the Report;*
- *copies of the Report (or extracts of the Report) may be distributed to contractors and agents of the organisation that commissioned the Report who have a need for the Report for its internal business operations. Any extracts of the Report distributed for this purpose must clearly note that the extract is part of a larger Report held by the organisation that commissioned the Report and which has been prepared by CSIRO.*

*The name, trademark or logo of the CSIRO must not be used without the prior written consent of CSIRO.*

*The Report must not be used as a means of endorsement without the prior written consent of CSIRO.*

## Copyright and disclaimer

© 2023 CSIRO To the extent permitted by law, all rights are reserved and no part of this publication covered by copyright may be reproduced or copied in any form or by any means except with the written permission of CSIRO.

## Important disclaimer

CSIRO advises that the information contained in this publication comprises general statements based on scientific research. The reader is advised and needs to be aware that such information may be incomplete or unable to be used in any specific situation. No reliance or actions must therefore be made on that information without seeking prior expert professional, scientific and technical advice. To the extent permitted by law, CSIRO (including its employees and consultants) excludes all liability to any person for any consequences, including but not limited to all losses, damages, costs, expenses and any other compensation, arising directly or indirectly from using this publication (in part or in whole) and any information or material contained in it.

# Contents

1	Introduction .....	6
1.1	Identification of specimen .....	6
1.2	Sponsor .....	6
1.3	Manufacturer(s) .....	6
1.4	Test standards .....	6
1.5	Test number .....	6
1.6	Test date .....	6
2	Description of specimen .....	7
2.1	General .....	7
	Wall Panels .....	7
	Wall construction .....	7
	Window .....	7
	Eaves	7
	Sill	8
2.2	Orientation .....	8
2.3	Crib size .....	8
2.4	Conditioning .....	8
2.5	Level of radiant heat exposure .....	8
2.6	Selection, construction and installation of the specimen and the supporting construction	8
3	Documentation .....	8
4	Equipment .....	9
4.1	Furnace .....	9
4.2	Temperature .....	9
4.3	Radiant heat source .....	9
4.4	Radiant heat flux calibration .....	9
4.5	Measurement system .....	9
5	Ambient temperature .....	9
6	Departure from standard .....	10
7	Termination of the test .....	10
8	Test results .....	10
8.1	Critical observations .....	10
8.2	Radiant heat flux .....	11
8.3	Specimen temperature .....	11
8.4	Performance .....	12
9	Tested by .....	12



Appendices ..... 13  
    Appendix A – Measurement location ..... 13  
    Appendix B – Test photographs ..... 14  
    Appendix C – Test data charts..... 23  
    Appendix D – Specimen drawings ..... 30  
References ..... 37

# Bushfire test on an external wall system

## Sponsored Investigation No. FSZ 2373

### 1 Introduction

#### 1.1 Identification of specimen

The sponsor identified the specimen as a Delta Panels external panel wall system.

#### 1.2 Sponsor

Delta Panels Pty Ltd  
731 Boundary Road  
Richlands, QLD 4077

#### 1.3 Manufacturer(s)

Manufacturer(s)	Product(s)
Delta Panels Pty Ltd	DeltaCool thermosetting phenolic core (TPC) insulated panels
Bradnam's Windows and Doors	BAL29 single glazed window

#### 1.4 Test standards

Australian Standard 1530, Methods for fire tests on building materials, components and structures;  
Part 8.1-2018: Tests on elements of construction for buildings exposed to simulated bushfire attack – radiant heat and small flaming sources.

Clause 15: Specific Procedures for External Wall Systems.

#### 1.5 Test number

CSIRO Reference test number FS 5267/4847

#### 1.6 Test date

The bushfire test was conducted on 11 May 2023.

## 2 Description of specimen

### 2.1 General

The specimen comprised a nominal 3000-mm wide x 2650-mm high x 100-mm thick external panel wall system, mounted on top of a 350-mm high non-combustible sill.

#### Wall Panels

The external wall system comprised 100-mm thick DeltaCool insulated panels. The panels consisted of thermosetting phenolic core (TPC) with a stated density of 38-42 kg/m<sup>3</sup>. The core was bonded on both sides to 0.6-mm thick roll formed steel skins using two-part polyurethane adhesive.

#### Wall construction

The wall specimen was constructed in accordance with the requirements stipulated in Section 15 of the AS1530.8.1-2018 test standard. The wall incorporated a rebate at the centre, with an internal and an external corner detail on each side of the rebate. The centre part of the wall included a window, with an eaves detail above it. The wall was constructed on top of a non-combustible sill with a representative wall to ground detail, as shown in drawings TPC-T001, sheets 1-4, dated 22 March 2023.

The wall corners were formed using 45-degree mitre joints, with the panels sealed with Soudal Firecyl FR sealant. The centre section of the wall included two panel joints, as it was constructed using three panels, one central 1200-wide panel and two 400-mm wide panels. The wall panels were joined together using slip joint design, and then sealed flush using Boss FireSilicone-EMA sealant.

All other joints including corner joints, panel edges and window surrounds were covered using steel corner and channel flashings fixed with steel rivets at 300-mm. All the flashings would then be sealed with a bead of Boss FireSilicone-EMA sealant.

#### Window

A Bradnam's "Essential" Series fixed window was installed in the central section of the wall specimen, approximately 500-mm off the bottom sill. The window incorporated clear 5-mm thick toughened glass framed in an 800-mm x 800-mm steel frame and was constructed in accordance with prescribed solution specified in AS 3959 for BAL 29. The window was face mounted on the fire exposed face of the wall into a close-fitting aperture cut out in the central wall panel, and restrained using steel angles and window flashings, as shown in drawing TPC-T001, sheet 3, dated 22 March 2023, and photograph 3 of Appendix B. The window flashings were fixed with steel rivets at 300-mm centres and sealed to the wall panels using Boss FireSilicone-EMA sealant.

#### Eaves

An eave detail was installed along the top of the rebate of the wall. The eave detail was constructed in accordance with prescribed solution specified in AS 3959 for BAL 29. It included a 250-mm x 250-mm metal framed boxed section lined on the front and the underside with 6-mm fibre cement sheeting. All the external corners of the eave framing were covered with corner flashings and sealed with Boss FireSilicone-EMA sealant.

## Sill

The wall was constructed on top of a non-combustible sill. The sill included a 350-mm x 350-mm metal framed boxed section lined with 6-mm fibre cement sheeting. The cavity of the framing was filled with Rockwool insulation.

## 2.2 Orientation

The external wall specimen was tested with the sill and the exterior face of the wall exposed to the radiant heat source.

## 2.3 Crib size

The crib size selected by the test sponsor for the relevant BAL level was Class AA, as specified in Table 3.2 of Section 3.8 of AS 3959:2018.

Three cribs were used, crib #1 was located in the internal corner of the wall rebate, Crib #2 was located adjacent to the panel joint left of the window, while crib #3 was located adjacent to the panel joint right of the window, as shown in Photograph 11 (Appendix B).

## 2.4 Conditioning

The external wall system did not include exposed timber elements.

The specimen construction was completed on 28<sup>th</sup> April 2022 and stored under standard laboratory atmospheric conditions until the test date.

## 2.5 Level of radiant heat exposure

The level of radiant heat exposure selected by the test sponsor was Very high - 29 kW/m<sup>2</sup>.

## 2.6 Selection, construction and installation of the specimen and the supporting construction

The construction was organised by the sponsor, CSIRO was not involved in the selection of the materials.

# 3 Documentation

The following documents were supplied or referenced by the sponsor as a complete description of the specimen and should be read in conjunction with this report:

- Drawings numbered TPC-T001, sheets 1-4, dated 22 March 2023, by Delta Panels.
- Drawings numbered TPC-T002, dated 15 February 2023, by Delta Panels.
- Drawings numbered TPC-T003, dated 15 February 2023, by Delta Panels.
- Drawings numbered TPC-T004, dated 22 March 2023, by Delta Panels.

No confidential information about the test specimen has been submitted to CSIRO Infrastructure Technologies

## 4 Equipment

### 4.1 Furnace

The furnace had a nominal opening of 3000-mm x 3000-mm for the attachment of vertical specimens.

The furnace was lined with refractory bricks and materials with the thermal properties as specified in AS 1530.4-2014 and was heated by combustion of a mixture of natural gas and air.

### 4.2 Temperature

The temperature in the furnace chamber was measured by eight type K, 3-mm diameter, and 310 stainless steel Mineral Insulated Metal Sheathed (MIMS) thermocouples. Each thermocouple was housed in high-nickel steel tubes opened at the exposed end.

Locations of the thermocouples on the unexposed face of the specimen are described in Appendix A.

### 4.3 Radiant heat source

The radiant heat source consisted of a 3-mm thick stainless-steel sheet mounted into a refractory frame in two sections with a vertical joint at its centre. The frame housing the steel sheet was positioned and sealed up against the front of the furnace aperture.

### 4.4 Radiant heat flux calibration

Prior to the test, the positions of the specimen (relative to the radiant heat source) were established that corresponded to the required radiant heat flux levels.

Radiation distribution was also established by measuring radiant heat flux levels at the centre and the centre of each quarter section of the specimen in a plane approximating the intended position of the specimen such that the central value will be approximately equal to the rest of the radiant heat flux.

### 4.5 Measurement system

The primary measurement system comprised multiple-channel data loggers, scanning at five second intervals during the test.

## 5 Ambient temperature

The temperature of the test area was 21°C at the commencement of the test.

## 6 Departure from standard

The specimen was left to cure under standard laboratory atmospheric conditions as opposed to a controlled environment of the average temperature of  $25 \pm 2$  deg C and relative humidity of  $45 \pm 5\%$ . The specimen was conditioned for a period of 5 days prior to testing, the requirements of AS 1530.8.1-2018 stipulates a minimum 7 days. The test laboratory confirms that the minor departure in conditioning would not have significantly affected the results of this test.

## 7 Termination of the test

The test was terminated at 61 minutes in accordance with the standard.

## 8 Test results

### 8.1 Critical observations

The following observations were made during the fire-resistance test:

- 0 minutes - Alight cribs placed in position.
- 25 seconds - Specimen moved in position – exposure to 29 kW/m<sup>2</sup>.
- 1:00 minutes - Smoke is emitted from the exposed face of the wall, flaming of the sealant along the panel joint adjacent to Crib #4.
- 2:25 minutes - Specimen moved in position – exposure to 21 kW/m<sup>2</sup>.
- 3:18 minutes - Crib #3 has ceased flaming.
- 3:25 minutes - Specimen moved in position – exposure to 14 kW/m<sup>2</sup>. Seals around the exposed side of perimeter of the window are starting to melt, photograph 10.
- 4:25 minutes - Specimen moved in position – exposure to 11 kW/m<sup>2</sup>. Crib #1 has ceased flaming.
- 5:10 minutes - Flaming of the sealant along the corner panel joint adjacent to Crib #1.
- 5:25 minutes - Specimen moved in position – exposure to 8 kW/m<sup>2</sup>.
- 5:50 minutes - Cribs #1 and #2 have ceased flaming.
- 6:25 minutes - Specimen moved in position – exposure to 7 kW/m<sup>2</sup>.
- 6:40 minutes - Smoke is observed on the unexposed side of the wall, adjacent to the corner crib #1.
- 7:45 minutes - Flaming on sealant in the corner, adjacent to crib #1 has ceased.
- 15 minutes - Radiant heat source shielded from the specimen. Radiometer is positioned 250-mm from the exposed face of the wall specimen in front of the inside corner, adjacent to crib #1. Cracks in the sealant along the panel joint adjacent to crib #2 have been observed, photograph 17.
- 17 minutes - No flaming, cracking or signs of any 3-mm through gaps.

- 20 minutes - Pilot flame was applied over the exposed face of the specimen – no ignition was noted at this time. 3-mm gap gauge applied to the specimen – No through gaps were noted.
- 58 minutes - Pilot flame was applied over the exposed face of the specimen – no ignition was noted at this time.
- 61 minutes - Test terminated.
- Post Test Inspection 3-mm gap gauge applied to the specimen – no through gaps were noted.

## 8.2 Radiant heat flux

Figure 1 shows the curves of target and incident radiation versus time recorded during the test period.

Figure 2 shows the curve of received radiation versus time at 250-mm from the exposed face of the specimen.

## 8.3 Specimen temperature

Figure 3 shows the temperature versus time recorded on the unexposed face of the wall.

Figure 4 shows the temperature versus time associated with crib 1.

Figure 5 shows the temperature versus time associated with crib 2.

Figure 6 shows the temperature versus time associated with crib 3.

Figure 7 shows the temperature versus time associated with the eave.

## 8.4 Performance

Performance observed in respect of Clause 14.4 of AS 1530.8.1-2018 criteria:

Performance Criteria	Time to failure (min)	Position of failure	
A gap from the fire exposed face to the non-fire exposed face greater than 3-mm	No Failure	-	
Sustained flaming for 10 seconds on the non-fire side	No failure	-	
Flaming on the fire-exposed side at the end of the 60 minutes test period	No failure	-	
Radiant heat flux 365-mm from the non-fire side exceeding 15-kW/m <sup>2</sup>	Not Applicable	-	
Mean and maximum temperature rises greater than 140 K and 180 K	No failure	-	
Radiant heat flux 250-mm from the specimen, greater than 3-kW/m <sup>2</sup> between 20 minutes and 60 minutes	No failure	-	
Mean and maximum temperature of internal faces exceeding 250°C and 300°C respectively between 20 minutes and 60 minutes after the commencement of the test	Not Applicable	-	
<b>Crib class</b>	<b>AA</b>	<b>Peak heat flux</b>	<b>29 kW/m<sup>2</sup></b>

For the purpose of building regulations in Australia, the test specimen achieved a **Bushfire Attack Level (BAL) of AA29**.

This report details the methods of construction, the test conditions and the results obtained when the specific element of construction described herein was tested in accordance with the test method of AS 1530.8.1.

## 9 Tested by

Chris Wojcik  
Testing Officer



# Appendices

## Appendix A – Measurement location

Measurement Location		
Group location	T/C Position	T/C designation
Unexposed Face	Top left quarter point – centre section	S1
	Top right quarter point – centre section	S2
	Bottom left quarter point – left wing wall	S3
	Bottom right quarter point – right wing wall	S4
	Centre – below window – centre section	S5
Unexposed face – crib locations	Crib- #1– corner crib – wing wall	S6
	Crib- #1 – corner crib – main wall	S7
	Crib- #2 – panel joint crib – main wall	S8
	Crib- #3 – panel joint crib – main wall	S9
Eaves	In line with corner crib #1	S10
	In line with panel joint crib #2	S11
	Centre	S12
	In line with panel joint crib #3	S13
Rover		
Ambient		

## Appendix B – Test photographs



**PHOTOGRAPH 1 – CONSTRUCTION OF SPECIMEN – FORMING UP OF THE TWO REBATE CORNERS**



**PHOTOGRAPH 2 – CONSTRUCTION OF SPECIMEN – INSTALLATION OF THE MAIN WALL SECTION**



**PHOTOGRAPH 3 – CONSTRUCTION OF SPECIMEN – INSTALLATION OF THE WINDOW FLASHING**



**PHOTOGRAPH 4 – CONSTRUCTION OF SPECIMEN – SILL DETAIL**





**PHOTOGRAPH 5 – CONSTRUCTION OF SPECIMEN – EAVES DETAIL**



**PHOTOGRAPH 6 – EXPOSED FACE OF THE SPECIMEN PRIOR TO TESTING**





**PHOTOGRAPH 7 – UNEXPOSED FACE OF THE SPECIMEN PRIOR TO TESTING**



**PHOTOGRAPH 8 – EXPOSED FACE OF SPECIMEN DURING 29 KW/M<sup>2</sup> EXPOSURE**





**PHOTOGRAPH 9 – EXPOSED FACE OF SPECIMEN DURING 21 KW/M<sup>2</sup> EXPOSURE**



**PHOTOGRAPH 10 – EXPOSED FACE OF SPECIMEN DURING 14 KW/M<sup>2</sup> EXPOSURE**





**PHOTOGRAPH 11 – EXPOSED FACE OF SPECIMEN DURING 11 KW/M<sup>2</sup> EXPOSURE**



**PHOTOGRAPH 12 – EXPOSED FACE OF SPECIMEN DURING 8 KW/M<sup>2</sup> EXPOSURE**





**PHOTOGRAPH 13 – UEXPOSED FACE OF THE SPECIMEN AT 7 MINUTES INTO THE TEST**



**PHOTOGRAPH 14 – EXPOSED FACE OF THE SPECIMEN AT 7 MINUTES INTO THE TEST**






**PHOTOGRAPH 15 – EXPOSED FACE OF SPECIMEN AT 12 MINUTES INTO THE TEST**



**PHOTOGRAPH 16 – EXPOSED FACE OF THE SPECIMEN AT 16 MINUTES INTO THE TEST**



**PHOTOGRAPH 17 – EXPOSED FACE ADJACENT TO CRIB #1 AND #2 AT 16 MINUTES INTO THE TEST**



**PHOTOGRAPH 18 – EXPOSED FACE OF THE SPECIMEN AT THE CONCLUSION OF TESTING**



Appendix C – Test data charts





FIGURE 1 – RADIANT HEAT FLUX



**FIGURE 2 – RADIANT HEAT FLUX RECEIVED AT 250-MM FROM THE EXPOSED FACE**







FIGURE 3 – TEMPERATURE VERSUS TIME ASSOCIATED WITH THE UNEXPOSED FACE OF THE WALL



**FIGURE 4 – TEMPERATURE VERSUS TIME ASSOCIATED WITH CRIB #1**



**FIGURE 5 – TEMPERATURE VERSUS TIME ASSOCIATED WITH CRIB #2**



**FIGURE 6 – TEMPERATURE VERSUS TIME ASSOCIATED WITH CRIB #3**






FIGURE 7 – TEMPERATURE VERSUS TIME ASSOCIATED WITH THE EAVE

# Appendix D – Specimen drawings

**Parts List**

ITEM	QTY	PART NUMBER	DESCRIPTION
1	1	DeltaCool-TPC-1	DeltaCool 10mm Thermosetting Phenolic Composite Core
2	1	DeltaCool-TPC-F02	DeltaCool 10mm TPC LH WALL
3	1	DeltaCool-TPC-F03	DeltaCool 10mm TPC RH WALL
4	1	TPC-TW02	TOP FRAME FOR FIBRO SHEET
6	4	TPC004	EXTERNAL CORNER FLASHING THIS DRAWING HAS LENGTH DETAILS FOR ALL
7	2	TPC005	CHANNEL FLASHING
8	4	TPC006	INTERNAL CORNER FLASHING THIS DRAWING HAS LENGTH DETAILS FOR ALL
9	2	TPC007	CHANNEL FLASHING
10	4	TPC008	CHANNEL FLASHING
11	4	TPC009	CHANNEL FLASHING THIS DRAWING HAS LENGTH DETAILS FOR ALL
12	2	TPC010	EXTERNAL CORNER FLASHING
13	1	TPC011	INTERNAL CORNER FLASHING
14	1	TPC012	WINDOW BRADMAN'S ESS FIXED 800mm
15	4	TPC013	CHANNEL FLASHING
16	4	TPC014	WINDOW FLASHING
25	2	TPC015	Fibro-cement sheet SEE SHEET 4
27	1	TPC017	Fibro-cement sheet SEE SHEET 4
28	1	TPC-TW05	

**6mm fibro-cement sheet on 3 sided**

**! NOTE !**

**APPLY SOLIDAL Firecyl FR THESE 4 INTERNAL/EXTERNAL CORNER FLASHINGS ONLY ALL OTHER FLASHINGS USE BOSS FireSilicone-EMA**

**6mm fibro-cement sheet on 4 sided**

**Cap corners with external corner flashing 3020 long**

Description  
Delta Panels TPS Test Wall


Designed by  
DP

Date:  
22.03/2023

Rev:  
C


Sheet  
1 / 4


**DRAWING NUMBERED TPC-T001, SHEET 1, DATED 22 MARCH 2023, BY DELTA PANELS**





Description Delta Panels TPS Test Wall	
Filename & Path E:\TPC\TPS Test Wall\TPC-T001.TPC	Date: 22/03/2023
Designed by DP	Rev: C
Drawing No. TPC-T001	Sheet 2/4


DRAWING NUMBERED TPC-T001, SHEET 2, DATED 22 MARCH 2023, BY DELTA PANELS




 <small>© COMPAGNIE DELTA PANELS</small> <small>Email: info@deltapanels.com</small>		Description <b>Delta Panels TPS Test Wall</b>
Filename & Path C:\Users\DP\Documents\Delta Panels\TPS Test Wall\TPC-T001.TPC	Date: 22/03/2023	Designed by DP
Drawing No. TPC-T001	Rev. C	Sheet 2/4

DRAWING NUMBERED TPC-T001, SHEET 3, DATED 22 MARCH 2023, BY DELTA PANELS






 <small>© COPYRIGHT 2023 DELTA PANELS Email: info@deltapanels.com</small>		Description Delta Panels TPS Test Wall
Filename & Path C:\Users\DP\OneDrive\Documents\Delta Panels\TPS Test Wall\TPC-T001.rvt	Date: 22/03/2023	Designed by DP
Drawing No. TPC-T001	Rev: C	Sheet 4 / 4


Parts List					
ITEM	QTY	PART NUMBER	DESCRIPTION	MATERIAL	SIZE
1	4	TPC-T002-RHS02		Steel, Mild	25x25x1.6RHS
3	4	TPC-T002-RHS02		Steel, Mild	50x3RHS
4	5	TPC-T002-RHS03		Steel, Mild	50x3RHS
5	4	TPC018		Steel, Mild	50x3RHS
6	3	TPC-T002-RHS04		Steel, Mild	25x25x1.6RHS



CONFIRM INSIDE DIMENSION OF ASSEMBLED PANEL STRUCTURE



QTY: 1



© COPYRIGHT RESERVED  
Email: info@deltapanels.com

**Description**  
TOP FRAME FOR FIBRO SHEET

**Filename & Path**  
D:\DELTA PANELS\FIBRO\Panel Test\tpc-t002.rvt

**Date:** 15/02/2023

**Designed by**  
Siven Djuve



**Drawing No.**  
TPC-T002

**Rev:** B


**Sheet**  
1/1



Parts List			
ITEM	QTY	PART NUMBER	SIZE
1	4	TPC-1002-RHS-01	40 x 40 x 1.618RS
2	4	TPC-1002-RHS-01	50x3PMS
4	4	TPC-1003-RHS-01	50x3PMS
5	9	TPC-1003-RHS-02	50x3PMS
6	5	TPC-1002-RHS-03	40 x 40 x 1.618RS



QTY. 1



DELTA  
PANELS  
© COPYRIGHT 2018 DELTA PANELS  
Email: info@deltapanels.com

---

Description: LOWER SUPPORT FRAME

Filename & Path: D:\DELTA PANELS\Projects\TPC-1003\TPC-1003-03.dwg


Date: 15/02/2023

Designed by: Siven Djuve

Drawing No: TPC-1003

Rev: B

Sheet: 1/1



PANELS FLUSH WITH FRAME FACE


HOT SIDE

FURNACE OPENING

M12 FEMALE THREADS AROUND OPENING  
AS PER DRAWING #457-7085



1 VIEW



COLD SIDE

TPC022  
ANGLE BRACKET  
FIT 5 EACH SIDE

Description	
Filename & Path C:\Users\DELTA\OneDrive\Documents\DELTA\TPC-004.dwg	Designed by DETAL-Sven Djuve
Date: 22/03/2023	Rev: B
Drawing No. TPC-T004	Sheet 1/1





# References

The following informative documents are referred to in this Report:

AS 1530.8.1-2018 Methods for fire tests on building materials, components and structures. Part 8.1: Tests on elements of construction for buildings exposed to simulated bushfire attack – Radiant heat and small flaming sources

AS 3959:2018 Construction of buildings in bushfire prone areas

\*\*\* end of report \*\*\*

#### CONTACT US

**t** 1300 363 400  
+61 3 9545 2176  
**e** enquiries@csiro.au  
**w** www.csiro.au

#### YOUR CSIRO

Australia is founding its future on science and innovation. Its national science agency, CSIRO, is a powerhouse of ideas, technologies and skills for building prosperity, growth, health and sustainability. It serves governments, industries, business and communities across the nation.

#### FOR FURTHER INFORMATION

##### **Infrastructure Technologies**

Brett Roddy

Team Leader, Fire Testing and Assessments

**t** +61 2 9490 5449

**e** brett.rodny@csiro.au

**w** <https://www.csiro.au/en/Do-business/Services/Materials-infrastructure/Fire-safety>