

Delta Cool EPS Panel Serviceability (L/150) Load Tables (kPa)					
	Thickness (mm)				
	50	75	100	150	200
1800	1.105	1.172	1.239		
2100	1.010	1.093	1.177		
2400	0.920	1.018	1.117	1.156	
2700	0.836	0.947	1.057	1.127	
3000	0.758	0.879	1.000	1.098	
3300	0.685	0.814	0.943	1.069	
3600	0.618	0.753	0.888	1.040	
3900	0.556	0.696	0.835	1.012	1.271
4200	0.500	0.641	0.783	0.983	1.247
4500	0.449	0.591	0.732	0.954	1.219
4800	0.404	0.543	0.683	0.925	1.187
5100	0.365	0.500	0.635	0.896	1.171
5400	0.331	0.459	0.588	0.867	1.127
5700	0.302	0.422	0.543	0.837	1.087
6000	0.279	0.389	0.499	0.808	1.067
6300	0.262	0.359	0.456	0.779	1.037
6600	0.250	0.332	0.415	0.750	1.007
6900	0.243	0.309	0.375	0.721	0.977
7200		0.169	0.337	0.692	0.947
7500		0.150	0.300	0.663	0.917
7800		0.132	0.265	0.634	0.887
8100		0.115	0.230	0.605	0.857
8400		0.099	0.198	0.576	0.827
8700		0.083	0.166	0.547	0.797
9000		0.068	0.136	0.518	0.767
9300			0.108	0.489	0.737
9600			0.080	0.460	0.707
9900			0.054	0.430	0.677
10200				0.401	0.647
10500				0.372	0.617