

Bushfire test on a roof system

Test Report

Author: Peter Gordon
Report number: FSZ 2411
Date: 21 December 2023

Clients: Delta Panels Pty Ltd

Commercial-in-confidence

Fire Testing and Assessments

Infrastructure Technologies
14 Julius Avenue
North Ryde, NSW 2113
Telephone +61 2 9490 5508

Author

Infrastructure Technologies
14 Julius Avenue
North Ryde, NSW 2113
Telephone +61 2 9490 5508




The Client

Delta Panels Pty Ltd
731 Boundary Road
Richlands, QLD 4077
Telephone +61 7 3271 2170

Report Status and Revision History:

VERSION	STATUS	DATE	DISTRIBUTION	ISSUE NUMBER
Draft	Draft	12/12/2023	CSIRO/Client	FSZ 2411
	Final for issue	21/12/2023	CSIRO/Client	FSZ 2411

Report Authorization:

AUTHOR	REVIEWED BY	AUTHORISED BY
Peter Gordon	Glenn Williams	Chris Wojcik
		
21 December 2023	21 December 2023	21 December 2023

Use of this Report

Use of Reports – Testing

This report is subject to binding obligations under which it was prepared. In particular, the Report must not be used:

- *as a means of endorsement; or*
- *in a company prospectus or notification to a Stock Exchange document for capital raising, without the prior written consent of CSIRO.*

The Report may be published verbatim and in full, provided that a statement is included on the publication that it is a copy of the Report issued by CSIRO.

Excerpts of the Report may not be published.

Use of Reports – Consultancy

This report is subject to binding obligations under which it was prepared. In particular, the Report may only be used for the following purposes:

- *the information in the Report may be used by the party that commissioned the Report for its internal business operations (but not licensing to third parties);*
- *the report may be copied for distribution within the organisation that commissioned the Report;*
- *copies of the Report (or extracts of the Report) may be distributed to contractors and agents of the organisation that commissioned the Report who have a need for the Report for its internal business operations. Any extracts of the Report distributed for this purpose must clearly note that the extract is part of a larger Report held by the organisation that commissioned the Report and which has been prepared by CSIRO.*

The name, trademark or logo of the CSIRO must not be used without the prior written consent of CSIRO.

The Report must not be used as a means of endorsement without the prior written consent of CSIRO.

Copyright and disclaimer

© 2023 CSIRO To the extent permitted by law, all rights are reserved and no part of this publication covered by copyright may be reproduced or copied in any form or by any means except with the written permission of CSIRO.

Important disclaimer

CSIRO advises that the information contained in this publication comprises general statements based on scientific research. The reader is advised and needs to be aware that such information may be incomplete or unable to be used in any specific situation. No reliance or actions must therefore be made on that information without seeking prior expert professional, scientific and technical advice. To the extent permitted by law, CSIRO (including its employees and consultants) excludes all liability to any person for any consequences, including but not limited to all losses, damages, costs, expenses and any other compensation, arising directly or indirectly from using this publication (in part or in whole) and any information or material contained in it.

Contents

1	Introduction	5
1.1	Identification of specimen	5
1.2	Sponsor	5
1.3	Manufacturer(s)	5
1.4	Test standards	5
1.5	Test number	5
1.6	Test date	5
2	Description of specimen	6
2.1	General	6
2.2	Orientation	7
2.3	Crib size	7
2.4	Conditioning	7
2.5	Level of radiant heat exposure	7
2.6	Selection, construction and installation of the specimen and the supporting construction	7
3	Documentation	7
4	Equipment	8
4.1	Furnace	8
4.2	Temperature	8
4.3	Radiant heat source	8
4.4	Radiant heat flux calibration	8
4.5	Measurement system	8
5	Ambient temperature	8
6	Departure from standard	8
7	Termination of the test	9
8	Test results	9
8.1	Critical observations	9
8.2	Radiant heat flux	9
8.3	Specimen temperature	10
8.4	Performance	10
9	Tested by	10
Appendices		11
Appendix A – Test photographs		11
Appendix B – Test data charts		21
Appendix C – Specimen drawings		24
References		39

Bushfire test on a roof system

Sponsored Investigation No. FSZ 2411

1 Introduction

1.1 Identification of specimen

The sponsor identified the specimen as a 45-degree pitched Delta Panels roof system that included a roof valley and a roof ridge detail.

1.2 Sponsor

Delta Panels Pty Ltd
731 Boundary Road
Richlands, QLD 4077

1.3 Manufacturer(s)

Manufacturer(s)	Product
Delta Panels Pty Ltd	DeltaTrim Thermosetting Phenolic Composite Insulated Panels (TPC)

1.4 Test standards

Australian Standard 1530, Methods for fire tests on building materials, components and structures;
Part 8.1-2018: Tests on elements of construction for buildings exposed to simulated bushfire attack – radiant heat and small flaming sources.

Clause 17: Specific Procedures for Roofs, Fascia and Gutter details.

1.5 Test number

CSIRO Reference test number FS 5305/4909

1.6 Test date

The bushfire test was conducted on 18 October 2023.

2 Description of specimen

2.1 General

The sponsor identified the specimen as a 45-degree pitched steel framed roof, clad with Delta Panels that measured nominally 2000-mm wide x 1550-mm deep that incorporated a 150-mm wide x 50-mm thick valley gutter located 450-mm from the right barge edge of the exposed face.

Supporting construction

The Delta Panels roof system was fixed to a DeltaTrim TPC test frame (TPC-R011) that measured 2040-mm wide x 880-mm deep x 1590-mm high at the back and 480-mm high at the front, fabricated using 65-mm x 65-mm SHS, 50-mm x 50-mm x 3-mm thick angled base and 1.2-mm BMT Beam cap (200-BEAM) located at the top, as shown in drawing number TPC-R011', dated 30 May 2023, by Delta Panel. The test frame was lined on both sides and the bottom with 6-mm thick fibre cement sheeting (TPC-R009 and TPC-R013) and a 100-mm thick DeltaCool -TPC insulated panel wall at the front.

Specimen Details

The roof was fabricated from three 100-mm thick DeltaTrim-TPC panels cut to 1550-mm length, the centre of the roof used a full width panel measuring 1000-mm wide (DeltaTrim-TPC Opp Cut), and two part width panels measuring 400-mm wide (DeltaTrim-TPC LH Cut) and 450-mm wide (DeltaTrim-TPC RH Cut) were used on the left and right hand edges of the roof respectively. The DeltaTrim-TPC panels comprised a thermosetting phenolic composite core (TPC) with a stated density of 38-42 kg/m³. The core was bonded on both sides to 0.6-mm thick roll formed steel skins using two-part polyurethane adhesive, the underside of the panel was flat, and the top steel skin had a Trimdeck profile, as shown in drawing 'DeltaTrim-TPC Opp Cut' dated 17/01/2018 by Delta Panels.

The bottom edge of the DeltaTrim-TPC panels were protected with profiled 1.2-mm thick roll formed steel skin DeltaTrim Fascia flashing (TPC-003) fixed with 13g x 25-mm self-drilling steel screws at 200-mm centres, and the exposed roof ribbing edges were covered with Delta TrimEnd Caps (TPC-R015) that were fully sealed with Boss FireSilicone-EMA sealant. The DeltaTrim-TPC panels were fixed to the steel frame using TEK 14 x 175 Hex screws and cyclone clips. All the joints on the underside of the roof were filled with a bead of FireSilicone-EMA sealant.

The left and right barge edges of the roof were fitted with x 0.6-mm thick roll formed profiled steel skin DeltaTrim 100-mm side barge trims (TPC-R006 and TPC-006-RH) fixed with TEK 14 x 175 Hex screws at 200-mm centres.

The right side of the roof incorporated a 150-mm wide valley gutter located 450-mm from the right barge edge. The valley gutter consisted of a 50-mm thick x 150-mm wide mineral wool core with a stated density of 38-42 kg/m³ covered on the top side with a 30-mm x 50-mm 150-mm wide x 0.6-mm thick roll formed steel skin (TPC-R005) fixed with Tex screws at 200-mm centres and a 230-mm wide x 0.6-mm thick roll formed steel skin Valley gutter flashing (TPC-R010) on the underside fixed with stainless steel rivets at 200-mm centres and the edges covered with FireSilicone-EMA sealant.

Located at the ridge of the roof was a x 0.6-mm thick roll formed profiled steel skin ridge cap (TPC-R014) fixed screws. All exposed gaps between the DeltaTrim-TPC panels and the ridge cap and the fibre cement sheeting on the sides were filled with a bead of FireSilicone-EMA sealant.

The roof specimen was fitted with a 120-mm wide x 140-mm high standard steel roof gutter.

The roof structure was enclosed at the back of the test frame with oriented strand board (OSB) that incorporated a 100-mm x 100-mm vent opening located at the base of the roof and a 200-mm x 200-mm glass vision panel.

2.2 Orientation

The roof specimen was tested with the exterior face of the roof exposed to the radiant heat source.

2.3 Crib size

The crib size selected by the test sponsor for the relevant BAL level was Class AA, as specified in Table 3.2 of Section 3.8 of AS 3959:2018.

Four cribs were used for the test, crib #1 was positioned in the roof gutter adjacent to the ridge edge of the valley gutter, while Cribs #2 and 3 were positioned in the valley gutter 700-mm and 1200-mm from the drip edge. Crib # 4 was positioned just below the ridge cap detail mid span as shown in Photograph 4 (Appendix A).

2.4 Conditioning

The roofing part of the specimen did not include exposed timber elements.

The specimen construction was delivered on 10th October 2023 and stored under standard laboratory atmospheric conditions until the test date.

2.5 Level of radiant heat exposure

The level of radiant heat exposure selected by the test sponsor was Very high - 29 kW/m².

2.6 Selection, construction and installation of the specimen and the supporting construction

The construction was organised by the sponsor, CSIRO was not involved in the selection of the materials.

3 Documentation

The following documents were supplied or referenced by the sponsor as a complete description of the specimen and should be read in conjunction with this report:

- Drawings reference 'Delta Trim TPC-RA01', sheets 1 and 2, Revision D, dated 30 May 2023, by Delta Panels.
- Drawings for various components '200 Beam', 'DeltaCool Wall', 'Delta Trim-TPC Opp Cut LHS', 'Delta Trim-TPC Opp Cut', 'Delta Trim-TPC Opp Cut RH', 'TCP-R001 to TCP-R015', 'TCP-R006-RH', 'TCP-R008-LH', by Delta Panels.

No confidential information about the test specimen has been submitted to CSIRO Infrastructure Technologies

4 Equipment

4.1 Furnace

The furnace had a nominal opening of 3000-mm x 3000-mm for the attachment of vertical specimens.

The furnace was lined with refractory bricks and materials with the thermal properties as specified in AS 1530.4:2014 and was heated by combustion of a mixture of natural gas and air.

4.2 Temperature

The temperature in the furnace chamber was measured by eight type K, 3-mm diameter, and 310 stainless steel Mineral Insulated Metal Sheathed (MIMS) thermocouples. Each thermocouple was housed in high-nickel steel tubes opened at the exposed end.

4.3 Radiant heat source

The radiant heat source consisted of a 3-mm thick mild steel sheet mounted into a refractory frame in two sections with a vertical joint at its centre. The frame housing the steel sheet was positioned and sealed up against the front of the furnace aperture.

4.4 Radiant heat flux calibration

Prior to the test, the positions of the specimen (relative to the radiant heat source) were established that corresponded to the required radiant heat flux levels.

Radiation distribution was also established by measuring radiant heat flux levels at the centre and the centre of each quarter section of the specimen in a plane approximating the intended position of the specimen such that the central value will be approximately equal to the rest of the radiant heat flux.

4.5 Measurement system

The primary measurement system comprised multiple-channel data loggers, scanning at five second intervals during the test.

5 Ambient temperature

The temperature of the test area was 21°C at the commencement of the test.

6 Departure from standard

There were no departures from the requirements of AS 1530.8.1-2018.

7 Termination of the test

The test was terminated at 60 minutes in accordance with the standard.

8 Test results

8.1 Critical observations

The following observations were made during the fire-resistance test:

- 0 minutes - Alight cribs placed in position.
- 29 seconds - Specimen moved into position – exposure to 29 kW/m².
- 2:36 minutes - Specimen moved into position – exposure to 21 kW/m².
- 3:29 minutes - Specimen moved into position – exposure to 14 kW/m².
Crib #1 (inside the gutter) has ceased flaming.
- 4:18 minutes - Crib #4 has ceased flaming.
- 4:29 minutes - Specimen moved into position – exposure to 11 kW/m².
- 5:29 minutes - Specimen moved into position – exposure to 8 kW/m².
- 6:47 minutes - Crib #3 has ceased flaming. Smoke is observed inside the roof cavity.
 - 7 minutes - Smoke is observed at the top of the roof.
 - 10 minutes - Smoke has ceased being emitted from the specimen.
 - 15 minutes - Radiant heat source shielded from the specimen. No flaming, cracking or signs of any 3-mm through gaps.
 - 16 minutes - Radiometer is positioned 250-mm from the centre of the exposed face of the roof specimen.
 - 20 minutes - Pilot flame was applied over the exposed face of the specimen – no ignition was noted at this time.
 - 33 minutes - Pilot flame was applied over the exposed face of the specimen – no ignition was noted at this time.
 - 60 minutes - Test terminated.

Post test, the back face of the roof assembly was removed to check for any gaps around the vents from inside the roof cavity. No through gaps >3-mm were found in the specimen.

8.2 Radiant heat flux

Figure 1 shows the curves of target and incident radiation versus time recorded during the test period.

Figure 2 shows the curve of received radiation versus time at 250-mm from the fire exposed face of the specimen.

8.3 Specimen temperature

Figure 3 shows the temperature versus time recorded on the non-fire side of the specimen.

8.4 Performance

Performance observed in respect of Clause 14.4 of AS 1530.8.1-2018 criteria:

Performance Criteria	Time to failure (min)	Position of failure	
A gap from the fire exposed face to the non-fire exposed face greater than 3-mm	No failure	-	
Sustained flaming for 10 seconds on the non-fire side	No failure	-	
Flaming on the fire-exposed side at the end of the 60 minutes test period	No failure	-	
Radiant heat flux 365-mm from the non-fire side exceeding 15-kW/m ²	Not Applicable	-	
Mean and maximum temperature rises greater than 140 K and 180 K	No failure	-	
Radiant heat flux 250-mm from the specimen, greater than 3-kW/m ² between 20 minutes and 60 minutes	No failure	-	
Mean and maximum temperature of internal faces exceeding 250°C and 300°C respectively between 20 minutes and 60 minutes after the commencement of the test	Not Applicable	-	
Crib class	AA	Peak heat flux	29 kW/m²

For the purpose of building regulations in Australia, the test specimen achieved a **Bushfire Attack Level (BAL) of AA29**.

This report details the methods of construction, the test conditions and the results obtained when the specific element of construction described herein was tested in accordance with the test method of AS 1530.8.1.

9 Tested by

Peter Gordon
Testing Officer

Appendices

Appendix A – Test photographs



PHOTOGRAPH 1 – THE ROOF CAVITY VIEWED FROM THE UNEXPOSED FACE OF THE SPECIMEN



PHOTOGRAPH 2 – SPECIMEN PRIOR TO TESTING



PHOTOGRAPH 3 – INSTRUMENTATION OF THE ROOF CAVITY



PHOTOGRAPH 4 – EXPOSED FACE OF THE SPECIMEN SHOWING CRIB LOCATIONS PRIOR TO TESTING



PHOTOGRAPH 5 – EXPOSED FACE OF SPECIMEN DURING 29 KW/M² EXPOSURE



PHOTOGRAPH 6 – EXPOSED FACE OF SPECIMEN DURING 24 KW/M² EXPOSURE



PHOTOGRAPH 7 – EXPOSED FACE OF SPECIMEN DURING 16 KW/M² EXPOSURE



PHOTOGRAPH 8 – EXPOSED FACE OF SPECIMEN DURING 12 KW/M² EXPOSURE



PHOTOGRAPH 9 – EXPOSED FACE OF SPECIMEN DURING 8.5 KW/M² EXPOSURE



PHOTOGRAPH 10 – EXPOSED FACE OF SPECIMEN DURING 7 KW/M² EXPOSURE



PHOTOGRAPH 11 – EXPOSED FACE SPECIMEN AT 5 MINUTES INTO THE TEST



PHOTOGRAPH 12 – EXPOSED FACE OF SPECIMEN AT 15 MINUTES INTO THE TEST




PHOTOGRAPH 13 – EXPOSED FACE OF SPECIMEN AT 15 MINUTES INTO THE TEST



PHOTOGRAPH 14 – EXPOSED FACE OF THE SPECIMEN AT 32 MINUTES INTO THE TEST



PHOTOGRAPH 15 – EXPOSED FACE OF THE SPECIMEN AT THE CONCLUSION OF TESTING



PHOTOGRAPH 16 – UNEXPOSED FACE OF THE ROOF CAVITY AFTER THE CONCLUSION OF TESTING



PHOTOGRAPH 17 – UNEXPOSED FACE OF THE ROOF CAVITY AFTER THE CONCLUSION OF TESTING



PHOTOGRAPH 18 – UNEXPOSED FACE OF THE ROOF CAVITY AFTER THE CONCLUSION OF TESTING



PHOTOGRAPH 19 – UNEXPOSED FACE OF THE ROOF CAVITY AFTER THE CONCLUSION OF TESTING

Appendix B – Test data charts




FIGURE 1 – RADIANT HEAT FLUX




FIGURE 2 – RADIANT HEAT FLUX RECEIVED AT 250-MM FROM THE EXPOSED FACE




FIGURE 3 – TEMPERATURE VERSUS TIME ASSOCIATED WITH THE UNEXPOSED FACE OF THE ROOF

Appendix C – Specimen drawings

fibro sheets not visible this view

DETAIL H
FIBRO SHEET FITS INSIDE ON ANGLES

ITEM	QTY	PART NUMBER	DESCRIPTION
1	1	TPC-R001	DeltaTrim-TPC TEST FRAME
2	1	DeltaCool-Wall	DeltaCool-TPC 100mm
3	1	TPC-R001	100mm DeltaCool CAP 45deg
4	1	DeltaTrim-TPC Top Cut	DeltaTrim-TPC 100mm 1000mm wide
5	1	200 BEAM	200 BEAM 2000 LONG
6	1	TPC-R002	BEAM CAP 45deg
7	1	TPC-R003	DeltaTrim FASCIA FLASHING
8	1	GUTTER	
9	1	DeltaTrim-TPC RH Cut	DeltaTrim-TPC 100mm Cut to size RHS
10	1	DeltaTrim-TPC LHS Cut	DeltaTrim-TPC 100mm Cut to size LHS
11	1	TPC-R010	VALLEY GUTTER FLASHING
12	1	TPC-R005	150mm VALLEY GUTTER
13	1	TPC-R006	DeltaTrim 100mm SIDE BARGE LH
14	1	TPC-R006-RH	DeltaTrim 100mm SIDE BARGE RH
15	1	TPC-R008	DeltaCool 100mm EDGE CAPPING
16	2	TPC-R009	6mm FIBRO SIDE PANEL
17	1	TPC-R012	DeltaCool 100mm BOTTOM CAPPING
18	1	TPC-R013	FIBRO SHEET 6mm 682mm x 1920mm
19	1	50mm MINERAL WOOL	50mm MINERAL WOOL Under Valley gutter
20	1	TPC-R016-LH	RIODE CAP
21	1	TPC-R014	
22	8	TPC-R015	DeltaTrim End Cap

DeltaTrim-TPC FIRE TEST MODULE

Date: 30/05/2023

Designed by: Sven Djulve


Rev: D

Sheet: 1/2

DeltaTrim-TPC-RA01


DELTA PANELS
© COPYRIGHT RESERVED
www.deltapanel.com

DRAWING TITLED 'DELTATRIM-TPC FIRE MODULE', SHEET 1, DATED 30 MAY 2023, BY DELTA PANELS




Description DeltaTrim-TPC FIRE TEST MODULE		Date: 30/05/2023	Designed by Sven Djurve
Fabricator & Part DELTA PANELS, RA000 Rev: 1.000 Rev: 1.000, PC: TEST 0005		Drawing No. DeltaTrim-TPC-RA01	Rev: D
		Sheet 2/2	



DRAWING TITLED 'DELTATRIM-TPC FIRE MODULE', SHEET 2, DATED 30 MAY 2023, BY DELTA PANELS




DRAWING NUMBER '200 BEAM', DATED 26 MAY 2023, BY DELTA PANELS




DRAWING NUMBER 'COOL WALL, DATED 23 JANUARY 2018, BY DELTA PANELS




LENGTH 1950.


 <p>DELTA PANELS © COPYRIGHT RESERVED Email: info@deltapanels.com</p>	Description DeltaTrim-TPC 100mm Cut to size LHS		
	Filename & Path E:\DELTA PANELS & PARTS\Panel Testing\DELTA000L TPC TEST\ROOF TEST\DeltaTrim-TPC Opp Cut LHS.dwg	Date: 17/01/2018	Designed by DP
	Drawing No. DeltaTrim-TPC Opp Cut LHS	Rev: 1	Sheet 1/1

DRAWING NUMBER 'DELTATRIM-TPC OPP CUT LHS', DATED 17 JAN 2018, BY DELTA PANELS




 <p>DELTA PANELS © COPYRIGHT RESERVED Email: info@deltapanels.com</p>	Description DeltaTrim-TPC 100mm 1000mm wide		
	Filename & Path E:\DELTA PANELS & PARTS\Panel Testing\DELTA000L TPC TEST\ROOF TEST\DeltaTrim-TPC Opp Cut.dwg	Date: 17/01/2018	Designed by DP
	Drawing No. DeltaTrim-TPC Opp Cut	Rev: 1	Sheet 1/1


DRAWING NUMBER 'DELTATRIM-TPC OPP CUT', DATED 17 JAN 2018, BY DELTA PANELS




DRAWING NUMBER 'DELTATRIM-TPC OPP RH CUT', DATED 17 JAN 2018, BY DELTA PANELS




DRAWING NUMBER 'TPC-R001', DATED 31MAY 2023, BY DELTA PANELS




LENGTH 2000
MATERIAL 1.2mm

 <p>© COPYRIGHT RESERVED Email: info@deltapanels.com</p>	Description 100mm DeltaCool CAP 45deg.		
	Filename & Path Z:\DELTA PANELS & PATIOS\Panel Testing\DELTA00L TPC TEST\ROOF TEST\TPC-R001.dwg	Date: 31/05/2023	Designed by Sven Djuve
	Drawing No. TPC-R001		Rev: B
			Sheet 1/1


DRAWING NUMBER 'TPC-R001', DATED 310MAY 2023, BY DELTA PANELS




LENGTH 2000
MATERIAL 1.2mm

 <p>© COPYRIGHT RESERVED Email: info@deltapanels.com</p>	Description BEAM CAP 45deg.		
	Filename & Path C:\DELTA PANELS & PARTS\Panel Testing\DELTA000_TPC TEST\ROOF TEST\TPC-R002.dwg	Date: 31/05/2023	Designed by Sven Djuve
	Drawing No. TPC-R002	Rev: A	Sheet 1/1


DRAWING NUMBER 'TPC-R002', DATED 31 MAY 2023, BY DELTA PANELS




LENGTH 2000
MATERIAL 1.2mm

 <p>© COPYRIGHT RESERVED Email: info@deltapanels.com</p>	Description DeltaTrim FASCIA FLASHING		
	Filename & Path C:\DELTA PANELS & PARTS\Panel Testing\DELTA000_TPC TEST\ROOF TEST\TPC-R003.dwg	Date: 31/05/2023	Designed by Sven Djuve
	Drawing No. TPC-R003	Rev: B	Sheet 1/1


DRAWING NUMBER 'TPC-R003', DATED 31 MAY 2023, BY DELTA PANELS




MATERIAL 0.6

 <p>© COPYRIGHT RESERVED Email: info@deltapanels.com</p>	Description 150mm VALLEY GUTTER		
	Filename & Path E:\DELTA PANELS & PATIOS\Panel Testing\DELTA0001 TPC TEST\WROOF TEST\TPC-R005.dwg	Date: 2/06/2023	Designed by Sven Djuve
	Drawing No: TPC-R005	Rev: B	Sheet 1/1


DRAWING NUMBER 'TPC-R005', DATED 2 JUNE 2023, BY DELTA PANELS




MATERIAL 0.6

 <p>© COPYRIGHT RESERVED Email: info@deltapanels.com</p>	Description DeltaTrim 100mm SIDE BARGE LH		
	Filename & Path E:\DELTA PANELS & PATIOS\Panel Testing\DELTA0001 TPC TEST\WROOF TEST\TPC-R006.dwg	Date: 31/05/2023	Designed by Sven Djuve
	Drawing No: TPC-R006	Rev: B	Sheet 1/1


DRAWING NUMBER 'TPC-R006', DATED 2 JUNE 2023, BY DELTA PANELS




DRAWING NUMBER 'TPC-R006-RH', DATED 2 JUNE 2023, BY DELTA PANELS




DRAWING NUMBER 'TPC-R008', DATED 31 MAY 2023, BY DELTA PANELS




DRAWING NUMBER 'TPC-R008-RH', DATED 31 MAY 2023, BY DELTA PANELS




DRAWING NUMBER 'TPC-R009', DATED 31 MAY 2023, BY DELTA PANELS




DRAWING NUMBER 'TPC-R010', DATED 30 MAY 2023, BY DELTA PANELS




DRAWING NUMBER 'TPC-R010', DATED 7 JUNE 2023, BY DELTA PANELS




DRAWING NUMBER 'TPC-R012', DATED 31 MAY 2023, BY DELTA PANELS



DRAWING NUMBER 'TPC-R013', DATED 1 JUNE 2023, BY DELTA PANELS



DRAWING NUMBER 'TPC-R014', DATED 31 MAY 2023, BY DELTA PANELS



DRAWING NUMBER 'TPC-R015', DATED 27 SEPTEMBER 2023, BY DELTA PANELS

References

The following informative documents are referred to in this Report:

- AS 1530.8.1-2018 Methods for fire tests on building materials, components and structures. Part 8.1: Tests on elements of construction for buildings exposed to simulated bushfire attack – Radiant heat and small flaming sources
- AS 3959:2018 Construction of buildings in bushfire prone areas

*** end of report ***

CONTACT US

t 1300 363 400
+61 3 9545 2176
e enquiries@csiro.au
w www.csiro.au

YOUR CSIRO

Australia is founding its future on science and innovation. Its national science agency, CSIRO, is a powerhouse of ideas, technologies and skills for building prosperity, growth, health and sustainability. It serves governments, industries, business and communities across the nation.

FOR FURTHER INFORMATION

Infrastructure Technologies

Keith Nicholls
Team Leader – Fire Assessments

t +61 2 94905450
e keith.nicholls@csiro.au
w <https://research.csiro.au/infratech/fire-safety/fire-testing/>